

**A**  
Hinges & Pivots



**B**  
Pulls & Plates

**C**  
Flush Bolts & Coordinators

Meets ANSI/BHMA 156.16, L11383 for brass and L31383 for aluminum.

**D**  
Latches, Catches & Bolts

**E16**  
Stops



**F**  
Exterior Hardware

Meets ANSI/BHMA 156.16, L11382 for brass and L31382 for aluminum.

**G**  
Miscellaneous Hardware

### FS452 Kick Down Holder

- Units provide simple hold and release, activated with a touch of the foot.
- Cast brass or aluminum construction.
- Stainless steel spring.
- Replaceable non-marring rubber shoes have corrugated bottoms to provide secure grip.
- Shoes are easily replaced when worn. Shoe held on with screw.
- Packed with sheet metal screws.

FS452-4 has a door-to-floor clearance of 2" or less.  
FS452-5 has a door-to-floor clearance up to 3".

#### Dimensions

FS452-4 Door-to-Floor Clearance: 2" or less

FS452-5 Door-to-Floor Clearance: Up to 3"

FS452-4 Plate Height: 2-1/8"

FS452-5 Plate Height: 2-1/8"

FS452-4 Plate Width: 1"

FS452-5 Plate Width: 1"

#### Finishes *brass*

Ives Number	US3	US4	US10	US10B	US15	US26	US26D
BHMA	605	606	612	613	619	625	626

#### Finishes *aluminum*

Ives Number	US28*
BHMA	628

\* available in 4" only

### FS455 Kick Down Holder

- Units provide simple hold and release, activated with a touch of the foot.
- Cast brass or aluminum construction.
- Replaceable non-marring rubber shoes have corrugated bottoms to provide secure grip. When worn, shoes are easily replaced. Shoe held on with screws.
- Door-to-floor clearances of 2" or less.

#### Dimensions

Door-to-Floor Clearance: 2" or less

Plate Height: 1-3/4"

Plate Width: 1-3/4"

#### Finishes *brass*

Ives Number	US3	US4	US5	US10	US10B	US15	US26	US26D
BHMA	605	606	609	612	613	619	625	626

#### Finishes *aluminum*

Ives Number	US3AL	US5AL	US10AL	US27
BHMA	666	609	668	673



FS544  
Meets ANSI/BHMA 156.16, L11381

FS555  
Meets ANSI/BHMA 156.16, L11391

## **FS544** **FS555 Kick Down Holder**

- Units provide an economical method to hold open doors.
- Cast of durable iron.
- Non-marring rubber shoes have corrugated bottoms to provide secure grip. Rubber shoe is securely fastened with screw. When worn, shoes are easily replaced.

FS544 for door-to-floor clearances of 2" or less  
FS555 for door-to-floor clearances up to 3".

### Dimensions

<b>FS544</b>	<b>FS555</b>
Door-to-Floor Clearance: 2" or less	Door-to-Floor Clearance: Up to 3"
Plate Height: 2-1/4"	Plate Height: 2-1/4"
Plate Width: 1-7/16"	Plate Width: 1-7/16"

### Finishes

Ives Number	SP4	SP10	SP28	SP313	SPBLK
BHMA	706	691	689	695	622

Hinges & Pivots  
**A**

Pulls & Plates  
**B**

Flush Bolts & Coordinators  
**C**

Latches, Catches & Bolts  
**D**

**E17**  
Stops

Exterior Hardware  
**F**

Miscellaneous Hardware  
**G**