



112XY Full Mortise - Narrow Frame and Door Leaf

UL10C certified

Meets ANSI 156.26 for 150 lbs and 300 lbs.

- For 1 3/4" Doors
- Patented center loaded, interlocking bearing design
- Non Handed for custom cut lengths
- Flush Mounted, No inset
- 48" Maximum Door Width
- Beveled or Square Edge Doors
- Frame guidance lip is extended further for retrofit applications to cover existing heavy weight architectural hinge preps
- For doors weighing up to 450 pounds without reinforcing, 600 pounds with reinforcing
- For lead-lined application consult factory for engineering specials

Standard lengths 83", 85", 95", 119"

Standard Mounting Hardware

12-24 x 3/4" Steel Self Drilling / Self Tapping Phillips Head Screw

Finishes

Clear Anodized (US28), Dark Bronze Anodized (313AN)

Custom Anodizing and Painting are available, consult factory

Options:

HT	Hospital Tip
EPT	Electric Power Transfer
TWP CON	Electrical Through Wire Panel with Allegion Connect

Optional Mounting Hardware:

TEK/WD	1/2 Self Drill, Self Tap 1/2 Wood
WD	Wood Door and Frame

Available Accessory Kits:

Security Screws - Hollow Metal
Security Screws - Wood
Thread Forming Screws

For Single Door Applications

For pairs of doors see chart and general information

