



Meets ANSI/BHMA A156.1  
A8122 – Steel  
A5122 – Stainless Steel  
A2122 – Brass

### 5BB1SC

### 5 Knuckle, Ball Bearing, Swing Clear Full Mortise Hinge

- For standard weight doors
- Square edge standard
- Medium frequency usage
- 2 ball bearing
- Packed with flat head wood and metal screws

*Designed to completely clear the opening when door is opened 92 degrees.*

#### Options

- NRP, Non-Removable Pin
- B, beveled edge door
- HT, Hospital Tip
- RC, Round Corners - 1/4" or 5/8" Radius
- SEC, Security Fastners - Pin-in-Socket

#### Dimensions

Size (Inches)	Size (mm)	Gauge
4.5	114	0.134
5	127	0.145



Meets ANSI/BHMA A156.1  
A8121 – Steel

### 5BB1SCHW

### 5 Knuckle, Ball Bearing, Swing Clear Heavy Weight Full Mortise Hinge

- For heavy weight doors
- High frequency usage
- 2 ball bearing
- Packed with flat head wood and metal screws

*Designed to completely clear the opening when door is opened 92 degrees.*

#### Options

- NRP, Non-Removable Pin
- B, beveled edge door
- HT, Hospital Tip
- RC, Round Corners - 1/4" or 5/8" Radius
- SEC, Security Fastners - Pin-in-Socket

#### Dimensions

Size (Inches)	Size (mm)	Gauge
4.5	114	0.180
5	127	0.190

#### Finishes *brass*

Ives Finish	US3	US4	US10	US10B	US10A	US11	US15	US26	US26D
BHMA	605	606	612	613	614	616	619	625	626

#### Finishes *steel*

Ives Finish	USP	US3	US4	US10	US10B	US10A	US11	US15	US26	US26D
BHMA	600	632	633	639	640	641	643	646	651	652

#### Finishes *stainless steel*

Ives Finish	US32	US32D
BHMA	629	630