

VON DUPRIN®

Exit devices

88 Series

Overview

The 88 Series is a wide style cross bar device. Rim, surface mounted vertical rod, concealed vertical rod and mortise configurations are available for panic and fire rated applications. The 88 Series features a non-handed design and flexible field sizing.



Device types



Rim device



75 Mortise lock device



27 Surface vertical rod exit device ¹



47 Concealed vertical rod device

¹ Also available less bottom rod (LBR)

Finishes



605
Bright Brass



606
Satin Brass



612
Satin Bronze



613
Oil Rubbed
Bronze



625
Bright Chrome




626
Satin Chrome



693
Black


Due to the many variations in monitors and printers, color samples may appear different than the physical product. Contact your local sales representative for a physical color sample.

Trim functions




EO No outside trim

- Exit only




DT Dummy trim

- Pull when dogged (not recommended for fire device)




NL Night latch

- Key retracts latchbolt
- Rim and 1 1/4" mortise cylinder




TP Thumbpiece

- Key locks and unlocks
- Rim and 1 1/4" mortise cylinder



TPBE Thumbpiece, blank escutcheon

- Blank escutcheon always operable (no cylinder, use with DT trim)



L Lever

K Knob


- Key locks and unlocks
- Rim and 1 1/4" mortise cylinder
- Handed, reversible lever
- Electrified lever operation available



LDT Lever, dummy trim

KDT Knob, dummy trim


- Pull when dogged



LNL Lever, night latch

KNL Knob, night latch

- Key retracts latchbolt
- Rim and 1 1/4" mortise cylinder
- Handed, reversible lever



LBE¹ Lever, blank escutcheon


KBE Knob, blank escutcheon

- Always operable (no cylinder)



TL Turn lever

- Key locks and unlocks (use with DT trim)
- 1 1/4" mortise cylinder



TLBE Turn lever, blank escutcheon

- Blank escutcheon always operable (no cylinder, use with DT trim)

Trim styles



880EO



880NL



880TP



880DT



880K



608DT



608NL



608TP



371L



373L



376T



377T

Trim styles

Dimensions

| Trim style | Width | Height | Projection |
|------------|-----------------------------------|-----------------------------------|-----------------------------------|
| 880EO | 3" | 14 ³ / ₁₀ " | N/A |
| 880NL | 3" | 14 ³ / ₁₀ " | 2" |
| 880TP | 3" | 14 ³ / ₁₀ " | 2" |
| 880DT | 3" | 14 ³ / ₁₀ " | 2" |
| 880K | 3" | 14 ³ / ₁₀ " | 2 ³ / ₄ " |
| 608DT | 1 ⁵ / ₈ " | 13 ¹ / ₂ " | 2 ¹ / ₆ " |
| 608NL | 1 ⁵ / ₈ " | 13 ¹ / ₂ " | 2 ¹ / ₆ " |
| 608TP | 1 ⁵ / ₈ " | 13 ¹ / ₂ " | 2 ¹ / ₆ " |
| 371L | 1 ¹¹ / ₁₆ " | 7 ¹ / ₂ " | 2 ⁵ / ₈ " |
| 373L | 1 ¹¹ / ₁₆ " | 7 ¹ / ₂ " | 2 ⁵ / ₈ " |
| 376T | 1 ¹¹ / ₁₆ " | 7 ¹ / ₂ " | 1 ¹³ / ₁₆ " |
| 377T | 1 ¹¹ / ₁₆ " | 7 ¹ / ₂ " | 1 ¹³ / ₁₆ " |

Lever styles

Standard levers



01



02

- Knurling available



03

- Knurling available



06

- Default lever
- Suites with Schlage Rhodes
- Knurling available



07

- Suites with Schlage Athens



12

- Handed




17

- Suites with Schlage Sparta
- Knurling available

Dimensions

| Lever | Width | Projection |
|-------|-------|------------|
| 01 | 4.0" | 2.1" |
| 02 | 4.75" | 2.3" |
| 03 | 4.75" | 2.813" |
| 06 | 4.7" | 2.1" |
| 07 | 4.6" | 2.3" |
| 12 | 4.3" | 2.9" |
| 17 | 4.7" | 2.3" |



Options

Electrified options

- RX Request to exit**
- Signals use of an opening
 - SPDT switch to monitor pushpad
 - 2 A maximum @ 24VDC; below 50 mA @ 24VDC for low current option

Electric unlocking

- E7500 Available on the following mortise lock devices: 8875L-BE, 8875L-BE-F**
- Voltage: 12 or 24VDC
 - Current: 0.6 amps @ 12VDC
 - 0.3 amps @ 24VDC

- E-trim Available as special order for the following BE trims: 371L-BE and E373L-BE**
- Voltage: 12 or 24 VDC
 - Current: 1.0 amps @ 12VDC
 - 0.5 amps @ 24VDC

Latches

- PL Pullman latch**
- Top and bottom latch for 8827 device (non-fire rated only)

Crossbar

- KN Knurled crossbar**
- Tactile warning applied to device
- RCB Reinforced crossbar**
- Fortified crossbar ideal for abusive environment.

Device options

Matrix shows available options per device type but does not represent compatibility across multiple options.

| | Electrified options | Electric unlocking | | | Latches | Crossbar | |
|--------|---------------------|--------------------|----------|----------|---------|----------|-----|
| | RX | E7500 | E371L-BE | E373L-BE | PL | KN | RCB |
| 88 | ▪ | | | ▪ | | ▪ | ▪ |
| 88F | ▪ | | | ▪ | | ▪ | ▪ |
| 8875 | ▪ | ▪ | | ▪ | | ▪ | ▪ |
| 8875-F | ▪ | ▪ | | ▪ | | ▪ | ▪ |
| 8827 | ▪ | | | ▪ | ▪ | ▪ | ▪ |
| 8827-F | ▪ | | | ▪ | | ▪ | ▪ |
| 8847 | ▪ | | ▪ | | | ▪ | ▪ |

Specifications

| | |
|------------------------------|--|
| Accessibility | <ul style="list-style-type: none"> ■ Cross bar projection <ul style="list-style-type: none"> - Neutral: 4 ³/₄" (121mm) - Depressed: 4" (102mm) |
| Certifications/ approvals | <ul style="list-style-type: none"> ■ ANSI/BHMA A156.3 2014 Grade 1 certified ■ ANSI/UL 10C (fire-rated only) ■ ANSI/UL 305 ■ CAN/ULC-S104 (fire-rated only) ■ CAN/ULC-S132 |
| Mounting height | <p>39 ¹³/₁₆" (1011 mm)</p> <p>39 ¹¹/₁₆" (1008 mm) with mullion</p> |
| Warranty | 36 months from the date of placing the product in operation |

Dimensions

